



Tubos LED T8 Alto Desempeño



Codigo	L	P	Vin	Color T	Flujo Lumínico (Φ _v)	Dimensiones	PF	THD	Base
OE-T8-600-8	600mm	8 W	90-277 Vac	6000K	850lm±10%	26 x 600mm	≥0.96	<10%	G13 R17D
				4100K	850lm±10%				
				3000K	810lm±10%				
OE-T8-600-10	600mm	10 W	90-277 Vac	6000K	1050lm±10%	26 x 600mm	≥0.96	<10%	G13 R17D
				4100K	1050lm±10%				
				3000K	900lm±10%				
OE-T8-1200-18	1200mm	18 W	90-277 Vac	6000K	2100lm±10%	26 x 1200mm	≥0.96	<10%	G13 R17D
				4100K	2100lm±10%				
				3000K	1900lm±10%				
OE-T8-1200-20	1200mm	20 W	90-277 Vac	6000K	2300lm±10%	26 x 1200mm	≥0.96	<10%	G13 R17D
				4100K	2300lm±10%				
				3000K	2100lm±10%				
OE-T8-1500-22	1500mm	22 W	90-277 Vac	6000K	2500lm±10%	26 x 2400mm	≥0.96	<10%	G13 R17D
				4100K	2300lm±10%				
				3000K	2200lm±10%				

Tabla de Equivalencias para reemplazo directo y un mismo nivel de iluminación.

Ölux LED	Flourescente	Ahorro
2 piezas T8 600mm 10 W	2 piezas T8 U 32W	44 W
1 piezas T8 1200mm 20 W	2 piezas T8 1200mm 32 W	44 W

