








Lámparas empotrables para plafón COB

Código	Foto	P	Vin	CCT	Flujo lumínico (Φ _v)	CRI	Ángulo de Haz	Diámetro Exterior	Diámetro Orificio
OE-DLC-3W-3"		3W	85-265 Vac	6000 K	360 lm	Ra ≥ 80	30° 45° 60°	85*65 mm	75-80 mm
				4100 K	330 lm				
				3000 K	300 lm				
OE-DLC-5W-3"		5W	85-265 Vac	6000 K	600 lm	Ra ≥ 80	30° 45° 60°	85*65 mm	75-80 mm
				4100 K	550 lm				
				3000 K	500 lm				
OE-DLC-7W-3"			85-265 Vac	6000 K	840 lm	Ra ≥ 80	30° 45° 60°	85*65 mm	75-80 mm
				4100 K	770 lm				
				3000 K	700 lm				
OE-DLC-9W-4"		9W	85-265 Vac	6000 K	1080 lm	Ra ≥ 80	30° 45° 60°	130*65 mm	115-120 mm
				4100 K	990 lm				
				3000 K	900 lm				
OE-DLC-12W-5"		12W	85-265 Vac	6000K	1440 lm	Ra ≥ 80	30° 45° 60°	160*80 mm	145-155mm
				4100 K	1320 lm				
				3000 K	1200 lm				
OE-DLC-15W-5"		15 W	85-265 Vac	3000 K	1800lm	Ra ≥ 80	30° 45° 60°	160*80 mm	145-155mm
				4100 K	1650 lm				
				6000 K	1500 lm				
OE-DLC-18W-6"		18 W	85-265 Vac	3000K	2160 lm	Ra ≥ 80	30° 45° 60°	190*80 mm	180mm
				4100 K	2050 lm				
				6000 K	1950 lm				
OE-DLC-20W-8"		20 W	85-265 Vac	3000K	2400 lm	Ra ≥ 80	30° 45° 60°	240*80 mm	220-230mm
				4100 K	2200 lm				
				6000 K	2000 lm				
PS-DL-30W-8"		30 W	85-265 Vac	6000K	3600 lm	Ra ≥ 80	30° 45° 60°	240*80 mm	220-230mm
				4100 K	3300 lm				
				3000 K	3000 lm				

Lámparas empotrables para plafón SMD Difusas

Código	Foto	P	Vin	CCT	Flujo lumínico (Φ_v)	CRI	Ángulo de Haz	Diámetro Exterior	Diámetro Orificio
OE-DLS-5W-4"		5 W	85-265 Vac	6000 K	500 lm	Ra ≥ 82	30° 45° 60°	85*65 mm	75-80 mm
				4100 K	475 lm				
				3000 K	450 lm				
OE-DLS-7W-4"		7 W	85-265 Vac	6000 K	700 lm	Ra ≥ 82	30° 45° 60°	85*65 mm	75-80 mm
				4100 K	665 lm				
				3000 K	630 lm				
OE-DLS-9W-5"		9 W	85-265 Vac	6000 K	1080 lm	Ra ≥ 82	30° 45° 60°	130*65 mm	115-120 mm
				4100 K	990 lm				
				3000 K	900 lm				
OE-DLC-12W-5"		12 W	85-265 Vac	6000 K	1080 lm	Ra ≥ 80	30° 45° 60°	130*65 mm	115-120 mm
				4100 K	990 lm				
				3000 K	900 lm				
OE-DLC-15W-6"		15 W	85-265 Vac	6000 K	1080 lm	Ra ≥ 80	30° 45° 60°	130*65 mm	115-120 mm
				4100 K	990 lm				
				3000 K	900 lm				